




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : H04L 25/06, 25/10	A1	(11) International Publication Number: WO 91/05427 (43) International Publication Date: 18 April 1991 (18.04.91)
---	-----------	---

(21) International Application Number: **PCT/US90/05358**(22) International Filing Date: **24 September 1990 (24.09.90)**(30) Priority data:
414,504 **29 September 1989 (29.09.89)** **US**(71) Applicant: **MOTOROLA, INC. [US/US]; 1303 East Algonquin Road, Schaumburg, IL 60196 (US).**(72) Inventor: **DEHNER, Leo, George, Jr. ; 1050 W. Ash #611, Euless, TX 76039 (US).**(74) Agents: **PARMELEE, Steven, G. et al.; Motorola, Inc., Intellectual Property Dept., 1303 East Algonquin Road, Schaumburg, IL 60196 (US).**(81) Designated States: **AT (European patent), BE (European patent), CA, CH (European patent), DE (European patent)*, DK (European patent), ES (European patent), FR (European patent), GB (European patent), IT (European patent), JP, LU (European patent), NL (European patent), SE (European patent).****Published**
With international search report.(54) Title: **METHOD OF DC OFFSET COMPENSATION USING A TRANSMITTED DC COMPENSATION SIGNAL**

(57) Abstract

A DC offset compensation method that makes use of a received DC compensation signal (107) having a known average value, such as zero. Differences between the known average value and the actually received average value are utilized to calculate a DC compensation value suitable for use in compensating subsequently received data information.

DESIGNATIONS OF "DE"

Until further notice, any designation of "DE" in any international application whose international filing date is prior to October 3, 1990, shall have effect in the territory of the Federal Republic of Germany with the exception of the territory of the former German Democratic Republic.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MC	Monaco
AU	Australia	FI	Finland	MG	Madagascar
BB	Barbados	FR	France	ML	Mali
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Fasso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GR	Greece	NL	Netherlands
BJ	Benin	HU	Hungary	NO	Norway
BR	Brazil	IT	Italy	PL	Poland
CA	Canada	JP	Japan	RO	Romania
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
DE	Germany	LU	Luxembourg	TD	Chad
DK	Denmark			TG	Togo
				US	United States of America

5

METHOD OF DC OFFSET COMPENSATION USING
A TRANSMITTED DC COMPENSATION SIGNAL

10 Technical Field

This invention relates generally to DC offset compensation of received data signals.

15 Background of the Invention

Transmission of data signals through various mediums is known in the art (as used herein, "data" refers to binary or multilevel signalling, as versus
20 analog signal waveforms). When receiving such a signal, it is not uncommon for a varying DC component to become combined therewith and possibly distort data recovery.

To compensate for this, various DC offset
25 compensation methodologies have been proposed. Although at least some of these prior art approaches can be implemented in a digital signal processor (DSP), such implementations require a relatively significant portion of the processing capacity of the DSP. This, in turn,
30 increases current drain requirements for the DSP and/or limits availability of the DSP for support of other desired functions.

Accordingly, a need exists for a method of DC offset compensation that will substantially reliably compensate for DC offset in a received data signal, and that may be implemented, if desired, in a DSP without
5 over burdening the processing capacity of the DSP.

Brief Description of the Drawings

Fig. 1 comprises a timing diagram of a
10 communication resource format implemented in accordance with the invention;

Fig. 2 comprises a depiction of a sync word waveform in accordance with the invention;

Fig. 3 comprises a block diagram of a receiver
15 constructed in accordance with the invention;

Fig. 4 comprises a depiction of a received sync word; and

Fig. 5 comprises a block diagram depiction of a part of the DSP operation when programmed in
20 accordance with the invention.

Best Mode For Carrying Out The Invention

For purposes of this description, an embodiment of
25 the invention will be described in conjunction with a time division multiplexed (TDM) communication resource. In this particular example, the frequency is subdivided into time frames, wherein each time frame is further subdivided into four time slots (101) (Fig. 1). In
30 a given time frame, two of the time slots (102) are used for the transmission of binary signalling information relevant to the allocation of the voice time slots (103) and other system control information.

Each control slot (102) in turn includes space for four commands (104), a slot designation (106), and a sync word (107).

In this embodiment, the sync word (107) is
5 comprised of the hex word zero nine D seven (09D7) (see Fig. 2). In binary form, as represented in Fig. 2, this equates with the sequential transmission of:
0000100111010111. Since this particular sync word, when represented in binary form, includes eight zeroes
10 and eight ones, the average value of the sync word equals zero.

In this embodiment, it will be presumed that the constituent elements of the sync word will be transmitted in a predetermined order, as set forth above,
15 with each broadcast. In a particular application, however, such a requirement may not be necessary. Also, in this particular embodiment, the average value of the sync word elements equals zero, and the importance of this will be made more clear below. (Other elements
20 could perhaps be used in an appropriate application, wherein the average value would not equal zero. What would be important in such an application, however, is that both the average value of the constituent elements of the sync word be predetermined and known to the
25 receiver, and that the system gain also be known to the receiver, since this gain would scale the non-zero average value.)

A receiver (300) (Fig. 3) suitable for practicing the method of the invention will now be described. This
30 receiver (300) includes an antenna (301) for receiving the signalling information (302) transmitted to it, including the data sync words (107). These signals (302)

are processed in an appropriate RF unit (303) and reduced to baseband. An analog to digital convertor (304) then digitizes this representation, and provides the digitized representation to a DSP (306) (such as a 5 56000 family device as manufactured and sold by Motorola, Inc.) where the signal can be demodulated and processed as desired. Voice transmissions received and processed in this way can then be reconverted to analog form by a digital to analog convertor (307), and the 10 resulting audio signal (308) can be further processed and amplified as appropriate to the particular application.

The receiver (300) further includes a processing unit (309) to control the operation of the RF unit (303) and of the DSP (306). In addition, the processing unit 15 (309) can receive and process recovered signalling information from the DSP (306). Also, an appropriate clock (311) provides necessary clock signals to the DSP (306) and processing unit (309), as may be appropriate to the particular application.

20 So configured, signals (302) received by the receiver can be processed in various programmable ways in the DSP (306). Such configurations, of course, are known in the art. In this particular embodiment, however, the DSP (306) processes samples (401) of the 25 received sync word (107) (see Fig. 4) at various times. The anticipated time of arrival of the sync word (107), and the constituent elements and order thereof, are of course known to the receiver (300). Therefore, by 30 comparing an average of the sampled values with the value that the receiver (300) would expect to find, the DSP (306) can calculate the difference. These differences can then be used to calculate a DC

compensation value suitable for use with subsequently received data.

In particular, the offset values calculated for this sync word, and also for previously received sync words, can effectively be averaged over time (501 and 502) (see Fig. 5) in the DSP to provide an estimated DC compensation value. As indicated earlier, this DC compensation value can then be used by the DSP to compensate for DC offset in subsequently received data information.

So configured, the DSP (306) is spared the necessity of constantly monitoring the received signal in support of an ongoing DC offset compensation calculation. Instead, by providing for reception of a sync word that effectively also operates as a DC compensation signal, having a substantially known average value, the DSP need only occasionally calculate a substantially reliable DC compensation value that can be used for DC compensation purposes.

What is claimed is:





Claims

1. A method of DC compensating a received signal, characterized by the steps of:

- 5 A) receiving a DC compensation signal having a substantially known average value;
- B) calculating a DC compensation value using the DC compensation signal.

2. The method of claim 1 wherein the known average value is approximately zero.
3. The method of claim 1 wherein the DC
5 compensation signal comprises a data packet.
4. The method of claim 3 wherein the data packet includes a binary representation of 0, 9, D, and 7.
- 10 5. The method of claim 4 wherein the binary representations of 0, 9, D, and 7 are organized in a predetermined manner.
6. The method of claim 3 wherein the known average
15 value of the data packet is zero.
7. The method of claim 1 and further characterized by the steps of:
 - A) receiving subsequent non-DC compensation
20 signals;
 - B) using the DC compensation value to DC compensate the non-DC compensation signals.
8. The method of claim 7 wherein the known average
25 value is approximately zero.
9. The method of claim 7 wherein the DC compensation signal comprises a data packet.
- 30 10. The method of claim 9 wherein the data packet includes a binary representation of 0, 9, D, and 7.

11. The method of claim 10 wherein the binary representations of 0, 9, D, and 7 are organized in a predetermined manner.
- 5 12. The method of claim 9 wherein the known average value of the data packet is zero.



INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US90/05358

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) ³

According to International Patent Classification (IPC) or to both National Classification and IPC

IPC (5) : H04L 25/06, 25/10

U.S. Cl : 375/36

II. FIELDS SEARCHED

Minimum Documentation Searched ⁴

Classification System :

Classification Symbols

U.S. 375/19; 358/171; 307/491; 328/168,173; 330/11

Documentation Searched other than Minimum Documentation
to the extent that such documents are included in the fields searched ⁵III. DOCUMENTS CONSIDERED TO BE RELEVANT ¹¹Category ⁶ Citation of Document, ¹² with indication, where appropriate, of the relevant passages ¹⁷ Relevant to Claim No. ¹³

X Y	P	US,A 4,873,702 (CHIU)	10 October 1989	1 & 7
		See the Abstract and Figure 2.		2-6 & 8-12
Y		US,A 4,387,364 (SHIROTA)	07 June 1983	2-6 & 8-12
		See Figures 4-7.		

¹⁴ Special categories of cited documents:¹⁵ "A" document defining the general state of the art which is not considered to be of particular relevance¹⁶ "E" earlier document but published on or after the international filing date¹⁸ "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)¹⁹ "O" document referring to an oral disclosure, use, exhibition or other means²⁰ "P" document published prior to the international filing date but later than the priority date claimed²¹ "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention²² "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step²³ "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.²⁴ "d" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search ²⁵

06 DECEMBER 1990

Date of Mailing of this International Search Report ²⁶

31 JAN 1991

International Searching Authority ²⁷

ISA/US

Signature of Authorized Officer ²⁸

 TESFALDET BOCURE